

IF14-2 SET-UP SHEET

NAME	
DATE	
TRACK	
EVENT	

QUAL. POSITION	FINAL POSITION	BEST LAP	RACE LENGTH
		sec	min

TEMPERATURE AIR	TEMPERATURE TRACK

TRACK	
TRACK SURFACE	☐ ASPHALT ☐ CARPET
TRACK LAYOUT	☐ TECHNICAL ☐ MIXED ☐ FAST
TRACTION	☐ LOW ☐ MEDIUM ☐ HIGH

FRONT	TRANSMISSION	REAR
☐ SOLID AXLE		
☐ GEAR DIFFERENTIAL	☐ GEAR DIFFERENTIAL	
OIL	OIL	
PINION GEAR	SPUR GEAR	FINAL DRIVE RATIO

FRONT	SHOCKS	REAR
☐ HARD ☐ SOFT	MEMBRANE	☐ HARD ☐ SOFT
	SPRINGS	
	OIL	
	REBOUND (%)	
☐ 3 HOLES ☐ 1.1mm	PISTONS	☐ 3 HOLES ☐ 1.1mm
☐ 4 HOLES ☐ 1.2mm		☐ 4 HOLES ☐ 1.2mm
	LENGTH	
	OTHER	

FRONT	TIRES	REAR
	TIRES	
	INSERTS	
	WHEELS	
	ADDITIVE	
	ADDITIVE TIMING	

MOTOR	TIMING
ESC	BATTERIES
BODY	WING

COMMENTS

WHEELBASE SHIM	BALANCE	TOP DECK	MAIN CHASSIS	BALANCE	WHEELBASE SHIM
FR mm	g	☐ STANDARD(2mm) ☐ 1.6mm	☐ STANDARD(2.25mm) ☐ ALUMINUM	g	RR mm
DIFF. POSITION	TOP DECK FLEX	SHIMS UNDER TOP DECK	TOP DECK FLEX	BALANCE	DIFF. POSITION
☐ UP ☐ DOWN ☐ STANDARD ☐ ALUMINUM	☒ SCREW USED ☐ SCREW NOT USED	☐ YES ☐ NO	☐ STIFF ☐ MEDIUM ☐ NO POST	g	☐ UP ☐ DOWN ☐ STANDARD ☐ ALUMINUM
WIDTH	BALANCE	WIDTH	BALANCE	WIDTH	WIDTH
mm	g	mm	g	mm	mm

FRONT	REAR
TOE OUT	TOE IN
deg.	deg.
BUMP STEER SHIM	ANTI-ROLL BAR
mm	mm
UNDER SHOCK SHIMS	ACKERMANN SHIM
LOWER mm UPPER mm	mm
CHASSIS STIFFENER	STEERING PLATE
☐ YES ☐ NO	☐ 8.0mm ☐ 8.5mm ☐ 9.0mm
SERVO HONE	MOTOR MOUNT, REAR STIFFENER FLEX
☐ STANDARD ☐ ALUMINUM ☐ 17mm ☐ 18mm ☐ 19mm ☐ 20mm	☒ SCREW USED ☐ SCREW NOT USED

FRONT	UPPER ARM MOUNT SPACER	SHIM	SHOCK MOUNT BUSHING	SHIM	STEERING BLOCK	FRONT ARM
	mm	mm	☐ 0 ☐ IN ☐ OUT ☐ 0.4 ☐ 0.8 ☐ 1.2	mm	☐ GRAPHITE ☐ HARD	☐ GRAPHITE ☐ HARD
ANTI-ROLL BAR	SUS. BLOCK	SUS. BLOCK SPACER	SUS. HOLDER SPACER	ECCENTRIC BUSHING	WHEEL HUB	CAMBER ANGLE
mm	FF ☐ 4.5 ☐ 4.5 FR ☐ 6.0 ☐ 6.0	FF mm FR mm	FF mm FR mm	FF ☐ 0.5 ☐ 1 ☐ 0.5 ☐ 1 FR ☐ 0.5 ☐ 1 ☐ 0.5 ☐ 1	☐ STANDARD (5.0) ☐ 4.5 ☐ 4.25 WHEEL SHIM mm	deg.
SUS. BLOCK	SUS. PLATE	DOWNSTOP	DRIFT	OTHER	DRIFT	DRIFT
FF mm FR mm	☐ 0 ☐ IN ☐ OUT ☐ 0.4 ☐ 0.8 ☐ 1.2	mm	mm		mm	mm

PRs SYSTEM Passive Rear Steering	C-HUB	SHIM	SHIM
	☐ ALUMINUM	mm	mm
STEERING BLOCK	☐ GRAPHITE ☐ HARD	SHIM	SHIM
WHEEL HUB	☐ STANDARD (5.0) ☐ 4.5 ☐ 4.25	mm	mm
WHEEL SHIM			

REAR	UPPER ARM MOUNT SPACER	SHIM	SHOCK MOUNT BUSHING	SHIM	REAR UPRIGHT	REAR ARM
	mm	mm	☐ 0 ☐ IN ☐ OUT ☐ 0.4 ☐ 0.8 ☐ 1.2	mm	☐ GRAPHITE ☐ HARD	☐ GRAPHITE ☐ HARD
ANTI-ROLL BAR	SUS. BLOCK	SUS. BLOCK SPACER	SUS. HOLDER SPACER	ECCENTRIC BUSHING	WHEEL HUB	CAMBER ANGLE
mm	RF ☐ 0.0 ☐ 4.5 RR ☐ 4.5 ☐ 6.0	RF mm RR mm	RF mm RR mm	RF ☐ 0.5 ☐ 1 ☐ 0.5 ☐ 1 RR ☐ 0.5 ☐ 1 ☐ 0.5 ☐ 1	☐ STANDARD (5.0) ☐ 4.5 ☐ 4.25 WHEEL SHIM mm	deg.
SUS. BLOCK	SUS. PLATE	DOWNSTOP	DRIFT	OTHER	DRIFT	DRIFT
RF mm RR mm	☐ 0 ☐ IN ☐ OUT ☐ 0.4 ☐ 0.8 ☐ 1.2	mm	mm		mm	mm