

## IF18-II SET-UP SHEET ver.1.0

<b>NAME</b>	DJ Apolaro
<b>DATE</b>	April 2021
<b>TRACK</b>	Steel City RC Speedway
<b>EVENT</b>	Protoform

<b>PINION</b>		<b>TRANSMISSION</b>		<b>SPUR</b>	
<input type="checkbox"/> 18T	<input checked="" type="checkbox"/> 19T	<input type="checkbox"/> 20T	<b>1ST</b>	<input type="checkbox"/> 60T	<input checked="" type="checkbox"/> 61T
<input type="checkbox"/> 23T	<input checked="" type="checkbox"/> 24T	<input type="checkbox"/> 25T	<b>2ND</b>	<input type="checkbox"/> 56T	<input checked="" type="checkbox"/> 57T
				<input type="checkbox"/> 62T	<input type="checkbox"/> 58T

<b>FRONT</b>		<b>SHOCKS</b>		<b>REAR</b>	
Cap Brown		<b>SPRINGS</b>		Cap Sedan Black	
500		<b>OIL</b>		5000	
<input checked="" type="checkbox"/> STD <input type="checkbox"/> OPTION		<b>O RING</b>		<input checked="" type="checkbox"/> STD <input type="checkbox"/> OPTION	
<input type="checkbox"/> STD <input type="checkbox"/> 2 HOLES		<b>PISTONS</b>		<input type="checkbox"/> STD <input type="checkbox"/> 2 HOLES	
mm		mm		mm	

<b>FRONT</b>		<b>ANTI-ROLL BAR</b>		<b>REAR</b>	
2.2		mm		3.0	
mm		mm		mm	

<b>FRONT</b>		<b>RIDE HEIGHT</b>		<b>REAR</b>	
6		mm		7	
mm		mm		mm	

<b>FRONT</b>		<b>WIDTH</b>		<b>REAR</b>	
251		mm		259	
mm		mm		mm	

<b>CONTROLLED</b>		<b>TIRES</b>		<b>BRAND</b>	
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO				HotRace	
<b>FRONT</b>		<b>REAR</b>			
<b>LEFT</b>	<b>RIGHT</b>	<b>LEFT</b>	<b>RIGHT</b>		
67	65	73.5	73	DIAMETER	
mm	mm	mm	mm	mm	

<b>FRONT</b>		<b>WHEEL PLATE</b>		<b>REAR</b>	
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO				<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	

<b>BODY</b>	
Extreme Diablo	

<b>BODY SETTING</b>	
<b>BODY POSITION</b> mm	
<b>FRONT CARBON PLATE</b>	
CARBON PLATE <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO (R0274)	
<b>REAR BODY MOUNT PLATE</b>	
<input type="checkbox"/> NO <input type="checkbox"/> 0.5mm <input checked="" type="checkbox"/> 1mm	
<b>BODY MOUNT SCREW</b> mm	
<b>BODY MOUNT CENTER FOAM</b> mm	

<b>SERVO SAVER</b>	
<b>STEERING PLATE</b>	
<input type="checkbox"/> 9mm <input type="checkbox"/> 10mm <input checked="" type="checkbox"/> 11mm (STD)	
<b>POSITION</b>	
FORWARD <input type="checkbox"/> MIDDLE <input checked="" type="checkbox"/> BACKWARD <input type="checkbox"/>	
<b>SERVO SAVER TYPE</b>	
<input type="checkbox"/> PLASTIC (R0006) <input type="checkbox"/> OPT (R0217) <input checked="" type="checkbox"/> OPT (R0259)	
<b>SPACER</b> mm	
2	
<b>TIGHTENING</b> mm	

<b>SHOCK TOWER</b>	<b>UPPER SUS HOLDER SIDE SCREW</b>	<b>UPPER SUS HOLDER &amp; POSITION</b>	<b>FRONT</b>
<input checked="" type="checkbox"/> STANDARD (R0081) <input type="checkbox"/> OPTION (R0081W)	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	<input checked="" type="checkbox"/> PLASTIC <input type="checkbox"/> PLASTIC (HARD) <input type="checkbox"/> ALUMINIUM	<b>CAMBER</b>
			.5 deg.
<b>UPPER PIVOT OFFSET</b>	<b>TOE OUT</b>	<b>MATERIAL</b>	<b>MATERIAL</b>
<input type="checkbox"/> -1.0 <input checked="" type="checkbox"/> 0 <input type="checkbox"/> +1.0	-1 deg.	<input checked="" type="checkbox"/> NORMAL <input type="checkbox"/> HARD	<input checked="" type="checkbox"/> NORMAL <input type="checkbox"/> HARD
<b>UPRIGHT ARM SPACER</b>	<b>SWING SHAFT</b>	<b>LOWER ARM HOLDER</b>	<b>DOWN STOP</b>
0 mm	<input type="checkbox"/> 60mm <input type="checkbox"/> 64mm <input type="checkbox"/> 60mm <input checked="" type="checkbox"/> 62mm (90°)	<input checked="" type="checkbox"/> PLASTIC <input type="checkbox"/> PLASTIC (HARD) <input type="checkbox"/> ALUMINIUM	+1 mm
<b>CASTER ANGLE</b>	<b>LOWER PIVOT TYPE &amp; SPACER HEIGHT</b>	<b>LOWER ARM PLATE</b>	
1 mm	<input type="checkbox"/> REVERSE 0mm=13.5 <input checked="" type="checkbox"/> NORMAL 0mm=15.5	<input checked="" type="checkbox"/> STANDARD (OUT SIDE) <input type="checkbox"/> OPTION (IN SIDE)	

<b>SHOCK TOWER</b>	<b>BODY MOUNT POSITION</b>	<b>REAR</b>
		<b>CAMBER</b>
		3 deg.
<b>CENTERING POSITION</b>	<b>UPPER SUS POSITION</b>	<b>REAR HUB SPACER</b>
<input checked="" type="checkbox"/> STANDARD <input type="checkbox"/> OPTION (REV)	<input type="checkbox"/> WIDE <input type="checkbox"/> NARROW	3 mm
mm		
<b>LOWER ARM HOLDER</b>	<b>SWING SHAFT</b>	<b>DOWN STOP</b>
<input checked="" type="checkbox"/> STANDARD <input type="checkbox"/> OPTION	<input checked="" type="checkbox"/> 54mm <input type="checkbox"/> 54mm(90°)	9 mm
<b>LOWER ARM PLATE</b>	<b>TOE IN</b>	<b>COMMENTS</b>
<input type="checkbox"/> IN SIDE <input type="checkbox"/> MIDDLE <input checked="" type="checkbox"/> OUT SIDE (STD)	1 deg.	Used 20 gram weight in bumper. Modified rear shock tower to make lower (more angle) in shocks - 1mm lower on the inner position.

<b>WEIGHT</b>	<b>CARBON STIFFENER</b>	<b>MAIN CHASSIS TYPE</b>	<b>CHASSIS</b>
<input type="checkbox"/> MIDDLE <input type="checkbox"/> RIGHT <input type="checkbox"/> LEFT	<input type="checkbox"/> FRONT CARBON (R0282) <input type="checkbox"/> MIDDLE CARBON (R0282)	<input checked="" type="checkbox"/> NORMAL (R0227) <input type="checkbox"/> SPECIAL (R0227M)	<b>UPPER PLATE TYPE &amp; CUT</b>
<b>ADDITIONAL WEIGHT</b>	<b>TOTAL CAR WEIGHT</b>	<b>BATTERY PLATE TYPE &amp; HOLD POSITION</b>	
g	2440 g		